Français Q

Technics

Products About us Where to buy Support



Direct Drive Turntable System SL-40CBT

Turntable Section

Drive Method	Direct Drive
Motor	Brushless DC motor
Turntable Speeds	33-1/3, 45
Build-up Characteristics	0.7 s. from standstill to 33- 1/3 rpm
Braking system	Electronic brake
Wow and Flutter	0.025% W.R.M.S.
Turntable Platter	Aluminium die-cast Diameter: 300mm(11-51/64")
	Weight: Approx. 1.26kg(2.78lbs) (Including Turntable mat)

Tonearm Section

Туре	Static Balance
Effective Length	230mm (9-1/16")
Overhang	15mm (19/32")
Tracking Error Angle	Within 2° 32' (at the outer groove of 30cm(12") record) Within 0° 32' (at the inner groove of 30cm(12") record)

Offset Angle	22°
Phono equalizer section	
Gain	36.5dB
Cartridge section	
Model Name	audio-technica AT-VM95C
Bluetooth® section	
Bluetooth® system specification	Bluetooth® Ver. 5.4
Wireless equipment classification	Class 1
Supported profiles	A2DP
Supported codec	Qualcomm [®] aptX™ Adaptive, SBC
Frequency band	2.4 GHz Band FH-SS
Operating distance	Approx. 10 m(33 ft) Line of sight*1 *1 Prospective communication distance。 Measurement environment: Temperature 25 °C(77 °F)/ Height 1.0 m(3.3 ft)
Terminals	
Audio Output	PHONO (Pin Jack) x 1 EARTH TERMINAL x 1 LINE (Pin Jack) x1
General	
Power Supply	AC120 V, 60 Hz
Power Consumption	4 W (Power ON) 0.2 W (Power OFF)
Dimensions (W x H x D)	430 x 128 x 353 mm (16-59/64" × 5-1/32" × 13-57/64") inch

Weight	Approx. 7.1kg 15.7lbs
Operating temperature range	0°C to +40°C (+32°F to +104°F)
Operating humidity range	35% to 80% RH (no condensation)
Accessories	Turntable, Turntable mat, Dust cover,
	EP record adaptor, Balance weight,
	Head shell with cartridge, PHONO cable,
	PHONO earth lead, AC power supply cord,
	Owner's Manual

Products DJ Equipment SL-40CBT

Facebook Twitter YouTube Instagram

Terms of use Privacy Policy Contact Us Cookies Policy

Copyright ©Panasonic Canada Inc.